

# C65WSD 2.7kW 13Amp



**Buttress Group Ltd.**  
Top Station Road, Brackley,  
Northants NN13 7UG, UK



C65WSD

↗	Overall dimensions (W x D x H)	mm	<b>575 x 700 x 850</b>
	Packaging dimensions (W x D x H)	mm	<b>670 x 780 x 1000</b>
	Gross weight	Kg	<b>66</b>
	Net weight	Kg	<b>61</b>
	Cubic volume	m <sup>3</sup>	<b>0.52</b>
☒	Rack size	mm	<b>500 x 600</b>
	Door opening	mm	<b>405</b>
	Max useable height	mm	<b>380</b>
	Rack guide rails		<b>embossed</b>
	Body construction		<b>stratified double skin</b>
🔥	Tank construction		<b>welded - stamped base</b>
	Tank volume	L	<b>23</b>
	Tank heating element	kW	<b>2.0</b>
	Surface scrap trays		<b>composite (2mm mesh)</b>
	Wash arms		<b>parallel Y (quick release)</b>
🌡️	Wash pump type		<b>dual flow</b>
	Wash pump power	kW	<b>0.7</b>
	Wash temperature	°C	<b>55 - 60 (adjustable)</b>
	Boiler type		<b>open</b>
🔥	Boiler volume	L	<b>6.0</b>
	Breaktank		<b>yes</b>
	Boiler heating element	kW	<b>2.0</b>
🌡️	Rinse booster pump		<b>yes</b>
	Rinse booster pump power	kW	<b>0.15</b>
	Rinse temperature	°C	<b>70 - 85 (adjustable)</b>
	Rinse arms		<b>parallel Y (quick release)</b>
🚰	Drain system		<b>partial drain</b>
	Drain filter		<b>triple filter</b>
	Drain pump		<b>yes</b>
💧	Rinse aid dispenser	peristaltic	<b>yes</b>
	Detergent dispenser	peristaltic	<b>yes</b>
🍷	Water consumption per cycle	L	<b>1.8 - 2.6</b>
	Inlet water pressure	bar	<b>0.5 - 6.0</b>
	Fast program (GLS1)	sec	<b>80</b>
	Total programs	programs	<b>9</b>
⚡	Total power	kW	<b>2.7</b>
	Electric connection	V-Ph-Hz	<b>230-240V 1N 50Hz</b>
	Alternative		<b>not convertible</b>
	Fuse	A	<b>13 (moulded plug)</b>
🔗	Water softener		<b>yes (continuous)</b>




## Supplied with

Flat rack	1
Plate rack	1
Cutlery rack	1
Electric cable	1
Drain hose	1
Fill hose	1

# C65WSD 2.7kW 13Amp



**Buttress Group Ltd.**  
Top Station Road, Brackley,  
Northants NN13 7UG, UK



All services must be within 1 metre