

THAWSAFE TECHNICAL DATASHEET

WTS75 THAWSAFE



WTS75

Dimensions (mm)	External	Internal
Width	727	567
Depth	941	807
Height	1960	1411
Door Opening		567

Capacity

Max load capacity (kg)	75
------------------------	----

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Easy to clean dished base with radiused corners
- Intuitive touchscreen controller with simple to operate icon based menu
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing door
- Precision injected, high density 75mm polyurethane insulation
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked door
- Product does not exceed 5°C throughout the thawing process
- Natural hydrocarbon refrigerant
- Fitted with 8 of 2/1GN nylon coated wire shelves
- Anti-tilt trayslides
- Cooking thawed food is quicker and safer than cooking from frozen - eliminating the risk of cold spots once cooking has finished
- Designed with forced air heating and cooling circuits which cycle alternatively keeping the food within the correct temperature range of 0°C to +5°C
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

OPTIONS

- Stainless steel back



THAWSAFE TECHNICAL DATA

ThawSafe	WTS75
Temperature (°C)	0/+5
Power Supply	220V/240V 50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic off cycle
Noise Level (dBA)	59

Fittings	
2/1GN Shelves (530 x 650mm)	8

Electrical Data - Standard Refrigerant	
Refrigerant	R290
Start Up (Amps)	6.8
Running (Amps)	6.8
Heat Rejection (kW / 24hrs)*	692
Power Input (kW)	0.63

IMPORTANT NOTES:

*Heat rejection is evaporating at -10°C in 32°C Ambient
 The WTS75 requires connection to a main drain
 All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
 Bryggen Road,
 North Lynn Industrial Estate
 King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
 Spares: +44(0) 1553 817 017
 E info@williams-refrigeration.co.uk
 W www.williams-refrigeration.co.uk

